

# MB 15 AK, MB 25 AK

## Spotřební díly



### Plynová hubice

	Ø A		Ø B	
cylindrická	Ø 16	145.0041	Ø 18	145.0042
kónická	Ø 12	145.0075 <sup>1</sup>	Ø 15	145.0076 <sup>2</sup>
silně kónická	Ø 9,5	145.0123	Ø 11,5	145.0124



### Proudová špička

		M6	M6
E-Cu	Ø 0,6	140.0008	-
	Ø 0,8	140.0059 <sup>1</sup>	140.0051
	Ø 1,0	140.0253	140.0242 <sup>2</sup>
	Ø 1,2	-	140.0379
E-Cu pro Al	Ø 0,8	141.0002	141.0001
	Ø 1,0	141.0007	141.0006
	Ø 1,2	-	141.0010
CuCrZr	Ø 0,6	140.0855	-
	Ø 0,8	140.0062	140.0054
	Ø 1,0	140.0256	140.0245
	Ø 1,2	-	140.0382

### Pružina



	002.0058 <sup>1</sup>	003.0013 <sup>2</sup>
--	-----------------------	-----------------------

### Mezikus / držák špičky



M6	002.0078 <sup>1</sup>	142.0001 <sup>2</sup>
----	-----------------------	-----------------------

Spirála / trubička		pro 3 m	pro 4 m	pro 5 m
	Spirála			
	Ø 0,6	124.0011	124.0012	124.0015
	Ø 0,8	124.0011 <sup>1</sup>	124.0012 <sup>1</sup>	124.0015 <sup>1</sup>
	Ø 1,0	124.0026 <sup>2</sup>	124.0031 <sup>2</sup>	124.0035 <sup>2</sup>
	Ø 1,2	124.0026	124.0031	124.0035
	PTFE-trubička			
	Ø 0,6	126.0005	126.0008	126.0011
	Ø 0,8	126.0005	126.0008	126.0011
	Ø 1,0	126.0021	126.0026	126.0028
	Ø 1,2	126.0021	126.0026	126.0028
	Uhlíko-PTFE-trubička			
	Ø 0,6	127.0002	127.0003	127.0004
	Ø 0,8	127.0002	127.0003	127.0004
	Ø 1,0	127.0005	127.0007	127.0008
	Ø 1,2	127.0005	127.0007	127.0008

<sup>1</sup> Standardní osazení u nového hořáku MB 15 AK.

<sup>2</sup> Standardní osazení u nového hořáku MB 25 AK.